

# airmagic<sup>®</sup>

THE BEST MACHINERY

## MP Series

## Portable Air Conditioning

MP03A



MP05A



**MAXIMUM** Efficiency  
**MINIMUM** Consumption

sige  
grupo

SPAIN | GERMANY | UNITED KINGDOM | FRANCE | ITALY | E.E.U.U. | MÉXICO | CHILE | PARAGUAY | ECUADOR

[www.airmagic.world](http://www.airmagic.world)

**IDEAL!**  
for TERRACES,  
swimming pools  
or open  
surfaces



**MP05A**

MP Series

**airmagic®**



- Terraces
- Restaurants
- Tents
- Congresses
- Events
- Sports Facilities





**ULTRA  
LOW  
CONSUMPTION**  
**100% ECO  
FRIENDLY**

**AIR  
QUALITY**  
at LOW  
COST



- Households
- Pool zone
- Lounges
- Gardens
- Bedrooms
- Small Surfaces



**MP03A**  
MP Series

**airmagic®**

# Technical Specifications

ESPECIFICATIONS	Airmagic®	MP03A	MP05A
Flow (m³/h)		5.000 m³/h	12.000 m³/h
Air Flow (m³/h)	SGS - Prodiex Certificate (Max. Work load)	3.417 m³/h	10.949 m³/h
Cooling Capacity	Total pressure capacity Active cooling	5,3 Kw	9,5 Kw
Energy Consumption	Med/Max kW-h	0,10 Kw/h	0,38 Kw/h
Ventilator Type	Self-Calibrated Turbo-Axial	Axial	Axial (3 blades)
Power Unit	Type	Normal	TorqueMax®
	Speed	3 speeds	3 speeds
	Voltage / Phases / Hz	220 / 1PH / 50Hz	220 / 1PH / 50Hz
	Overload	Protection with overload restored	Protection with overload restored
	Refrigeration - Insulation	Self Cooling IP24	Self Cooling IP24
	Case	Sealed Faith	Sealed Faith
	Rotor	Standard	Industrial
Pumps	Coil/ Thermal Capacity	Copper / 120°C	Copper / 120°C
	Double pump / Double Circuit	Simple Circuit	Simple Circuit
	Protection with Overload	Yes	Yes
	Type	Centrifuge	Centrifuga sumergible
	Flow Rate	2 - 3 L/h	6 - 10 L/h
Cooling Panels	Functioning	Variable according to speed	Variable according to speed
	Tipology	MagicPanelEvo-I®	MagicPanelEvo-I®
	Proportions (mm)	[2x(160x400)]+(400x500)	[2x(180x680)]+(680x680) (3p)
	Effective Cooling Area	0,328m²	0,707m²
Water Systems	Drop Drag	Anti Drag Design	Anti Drag Design
	Capacity / Optimal Consumption	25L	58L (Smart Water Management)
	Water Purifier System	Conventional	Antibac-UV® (Airmagic Exclusive)
Proportions and Noises	Size (mm)	957x493x364	1.385x800x485
	Weight	11,3 Kg	30 Kg
	Exit Duct without Reduction	Diffusion in machine	Diffusion in machine
	Noise	50dB (A)	56dB (A)
	Case: PP Polymers, Anti- UV	High Quality Plastic	High Quality Plastic
Control Systems	Fixed Wall Control	No	No
	Remote Control	Yes	Yes

## Thecnical and Commercial Assistance



+34 924 312 514



info@airmagic.es  
www.airmagic.es

### GUARANTEES:



Anti-corrosion  
guarantee for  
external covers



Guarantee  
structural  
components



Guarantee for  
electronic engine and  
pump control  
module

### AWARDS:



PRIZE  
NEEEx 2007  
BUSINESS  
TRAJECTORY



PRIZE  
BUSINESSMAN  
Extremadura 2010  
INNOVATION



PRIZE  
EJECUTIVOS 2018  
TECHNOLOGICAL  
DEVELOPMENT

### CERTIFICATES:



Apragaz

