



Microchannel for HVAC/R

ThermoKey®
Heat Exchange Solutions



In the next 5 years aluminium microchannel cores will replace 50% of the copper coils for HVAC/R application. We are ready to take on the role of key player.

Giuseppe Visentini — Executive Board Member — COO, ThermoKey Spa



TKMicro
is the best solution for HVAC/R.

European Leader

ThermoKey has been producing heat exchangers since 1991. Since then it has gained a key player role, becoming partner to the major chiller manufacturers in the European Market.

What the market asks for

Knowledge

Our customers must compete to meet the always more and more sophisticated needs of the market. The challenge is on knowledge: metallurgic, thermodynamic, mechanic, acoustic and electronic. Our customers have to be able to count on a partner capable of answering with knowledge to the new challenges.

Innovation

Innovation is the central issue in economic prosperity (Porter). In the HVAC/R market this means manufacture known products in an innovative way and new products and services.
The most appreciated goals by the market are those which lead to the reduction of waste for the entire life of the product.

Reliability

Reliable Companies that respect sales contracts and whose products are in accordance with their use function throughout time.

Saving

A quick come back of the initial investment is the key in the Service market and to win competition against products of the low range. However saving is also the reduction in the use of the natural resources of the planet.

ThermoKey answers

European knowledge leader

Since 2009 ThermoKey has been investing in microchannel technology and it has developed its own know-how by working together with its qualified supply chain and with the best pioneer customers in order to learn how to manage the manufacturing process of its products.

Cutting-edge technology

ThermoKey has invested to offer a solution studied especially for the HVAC/R market starting from an automotive technology. The result is an heat exchanger which, with its innovative characteristics of lightness and thickness, can deeply change the actual offer available to our customers.

Long lasting products

TKMicro is installed on thousands of units which work efficiently. Materials, thicknesses and the manufacturing process have been especially defined to be the best solution on the market. The durability and the constant performance in time contribute to the quick come back of the initial investment.

Eco-sustainability and efficiency

TKMicro is composed of 100% recyclable materials. Compared to tube and fin technology TKMicro weighs almost 60% less (compact foot-print and weight) and needs much less refrigerant. Its geometry drastically reduces pressure drops leading to energy saving and reduction of the acoustic impact.



Values

THERMOKEY MICROCHANNEL IS DIFFERENT


- Unique cores optimized for HVAC and refrigeration markets.
- Unique high-quality condensing cores which can reach up to 6 meter length.
- Unique cores designed to allow energy saving (45% saving by reducing pressure drops).

100% CUSTOMIZED ALLOYS DESIGNED FOR MAXIMUM PERFORMANCE

ThermoKey engineers have optimized the design of all the geometrical details of the 100% alloy cores in order to ensure the best compromise between thermodynamics performance, pressure drop and lightness. These features make ThermoKey cores the most efficient in the market.

THERMOKEY MICROCHANNEL TECHNOLOGY

- The highest resistance of aluminium LLA (Long Life Alloy) to corrosion (SWAAT Test over 80 days in accordance with the ASTM G85-02 norm) ensures reliability and performance.
- Thickness and configuration, unique on the market, make it more resistant to vibrations, water hammer and corrosive environments.
- The peculiar header shape reduces pressure drops on the refrigerant side and allows the use of a single circuit.
- Suitable to all standard refrigerants (R410A, R134a, R22, R407C, R404A, R290, R507A, R245fa ect..).
- The low pressure drops of TKMicro cores available in every size (up to 6 meters) allow to satisfy the needs of high-performance chiller manufacturers.
- Easy cleaning and maintenance.
- In case of need ThermoKey can provide a kit for a quick and easy repair to be used directly on site.



Maximum dimension 1,3 mt height, 6 mt length

TKMicro


comparison with round-tube technology

More efficiency

In comparison to the top quality 4 rows round tube coil, TKMicro offers great advantages in terms of performance.

DOUBLE VERSION, SAME RELIABILITY

TKMicro has been designed in two versions: 32mm MPE and the new 25mm MPE which maintains same top quality.



PRECONDITIONS

Face Area (H x L)	1.200mm x 2.000mm
Air Flow	25.000 m³/h
Delta Temperature	15°C

- TKMicro
- Round Tube Cul/Al

More reliability


Constant performance over time even in the most aggressive environments. Comparison between round tube technology and TKMicro.

TKMICRO GUARANTEES CONSTANTS PERFORMANCES THROUGHOUT TIME

The accurate choice of the materials supplied by the best manufacturers, the control over the manufacturing process and the attention given to every single detail make TKMicro the most reliable core on the market.

TKMicro has brilliantly performed in the SWAAT Test (ASTM G85-02 norm) resisting over 80 days.

Results certified by 2 independent laboratories obtaining the same results of a traditional coil (CU/AL).





SWAAT TEST

80 days ASTM G85 - 02 norm (laboratory certified data).

- TKMicro
- Round Tube Cul/Al

TKMicro technology



THERMOKEY MICROCHANNEL TECHNOLOGY

ThermoKey has chosen the top class materials available to ensure the maximum quality for its TKMicro technology. All core details are developed together with the best supplier on the market in order to answer to the specific requirements of HVAC/R market.

MULTI PORT EXTRUDED (MPE)

MPE tubes allow the best heat transfer with the minimum dimensions. We provide two different types of MPE tubes to better fit the need of our customers. Both tubes have the greatest wall thickness on the market (0,5 mm) in order to ensure robustness and corrosion resistance.

TKMicro25: 25mm width

The best compromise between performance and lightness.

TKMicro32: 32mm width

Ideal to the low pressure drop and the maximum heat transfer. Particularly suitable for application with high air flow rate.

FIN

Using Finite Element Analysis (FEA) technique and our Wind Tunnel facility, we have optimized louvered angles, fin pitch and the number of louvers in order to achieve minimum air side pressure drop and, at the same time, maximize the air heat transfer.

We produce fins that fit both the 32mm tube and the 25mm tube. The brazing process ensures a perfect and permanent contact between tubes and fins.

HEADER




D-shape header

- For its most demanding customers ThermoKey also provides the D-shape header with 3mm wall tickness. The D-shape has lower pressure drops and is specifically designed for chiller manufacturers.
- Best distribution of refrigerant inside the core.
- Lower pressure drops.
- Best performance of the core.

Upon request, we are also able to provide headers expressly developed to meet the demands of UL Certification.

Round header

The round header with 2,3mm wall tickness is the best selling header on the market and it is particularly suitable for R410A applications thanks to its excellent pressure resistance.




Efficiency in the production line

Our semi-continuous line is manufactured to fit a wide range of dimensions: we can manufacture cores with length from 400mm to 5800mm and height from 300mm to 1300mm.

ThermoKey has chosen the latest generation of Controlled Atmosphere Brazing (CAB) Furnace for the manufacturing of its aluminium heat exchanger.

The fully automated furnace is provided with an array of sensors distributed all over the line to guarantee control and stability of the brazing process.



ThermoKey Know-How

Enviroment safety of all the process

The line is provided with a scrubber for the filtering of the hydrofluoric acid.

10,000 m2 production site

Totally dedicated to aluminium on an overall settlement of 16,700 m2

State-of-the-art production process

It can produce a 4 meter core every 7 minutes.

5 years of lab and field testing

Testing performances with different refrigerants, different surface treatments and at different working conditions.



How to use TKMicro for HVAC/R



HORIZONTAL MODE
Standard series.



VERTICAL MODE
Maximum modularity.








FREE COOLING APPLICATION
Standard round tube coil+ TKMicro.



MULTIPLE HORIZONTAL MODE
Maximum performance with the minimum foot-print.




UPSIDEDOWN "M" SHAPE
Specific for R134a chiller manufacturers.




TKMicro Research and development


ThermoKey is constantly involved in an ongoing activity to develop new products and solutions. Every detail is studied to optimize performances. To guarantee always the best quality our engineers are working on several aspects:



STRUCTURAL CALCULATION
Through FEM analysis we are able to foresee material deformations and work on possible problems before these occur.



AIR-FLOW SIMULATIONS
The air flow performance of the TKMicro cores is tested through an especially built Wind Tunnel which is able to reach 22,000m³/h.



THERMO-FLUID-DYNAMIC ANALYSES
The thermodynamic performance is maybe the most important information for our customers. To obtain always more reliable data we realize CFD simulations of the fluid distribution inside the heat exchanger and we constantly verify the accuracy.

TKMicro

Microchannel Remote Condensers

Thanks to a consolidated know-how in the heat exchanger production, ThermoKey is able to maximize the competitive advantages of microchannel technology, offering a series of remote condensers.

- +30% capacity vs same foot-print traditional condensers.
- Modular design, 1-8 fans.
- Reduced dimensions and weight.



TABLE REMOTE CONDENSER

Performance range
capacity from 10 kW to 480 kW(*)

Fans
diameter Ø 300, 400, 450, 500, 630, 800, 900 mm,
AC or EC motor



V-TYPE REMOTE CONDENSER

Performance range
capacity from 90 kW to 870 kW (*)

Fans
diameter Ø 800, 900 mm, AC or EC motor

(*) **Standard conditions** - R404A, condensing temp: 40°C,
subcooling: 3°K, desuperheat: 25°K, air temp: 25°C



TKSMART (LIGHT REMOTE CONDENSER)
Performance range
capacity from 13 kW to 98 kW(*)

Fans
diameter Ø 400, 500, 630 mm, AC or EC fans

TKArchimede

selection software

CALCULATION FUNCTION

Entry working conditions (requested capacity, temperature and type of the fluid, noise level and eventual other plant restrictions).

VERIFY FUNCTION


It is possible to verify the performances of each unit in one or more specific working conditions.

TKARCHIMEDE SELECTS THE UNITS ACCORDING TO PARAMETERS:

- main **fluids** present on the market;
- **altitude, humidity, inlet air temperature;**
- **fins** thickness (automatic adjustment of capacity);
- different range of **accessories** available:



Direction
Acrobatik
—
Photography
Cover: **Matteo Lavazza Seranto**
3° Cover, p.6-12-21: **Emiliano Lucchetta - Acrobatik**
—
Printed in Italy by
Grafiche Filacorda
—
TKM0216EN



ThermoKey®
Heat Exchange Solutions

ThermoKey Spa
via dell'Industria, 1 - 33061
Rivarotta di Rivignano Teor (UD) - Italy

T. +39 0432 772300
F. +39 0432 779734
info@thermokey.com
www.thermokey.com

