

RENISO TRITON SEZ 68

**Synthetic refrigeration oil based on polyol esters (POE)
for HFC/FC and HFO refrigerants – including HFO/HFC
refrigerant blends**

Typical data:


Product name		RENISO TRITON SEZ 68	
Properties	Unit		Test method
Density at 15 °C	kg/m ³	972	DIN 51757
Flash point	°C	258	DIN ISO 2592
Colour	-	0.5	DIN ISO 2049
Kinematic viscosity at 40 °C	mm ² /s	68	DIN EN ISO 3104
at 100 °C	mm ² /s	8.9	
Viscosity index	-	104	DIN ISO 2909
Pourpoint	°C	-39	DIN ISO 3016
Neutralisation number	mgKOH/g	0,03	DIN 51558-1
Water content	mg/kg	< 50	DIN 51777-2

Please find more information about the complete range of synthetic polyolester oils (POEs) on Product Information sheet: PI 4-1255 / RENISO TRITON SE/SEZ Series.

RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends

Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R134a





PI 4-1332, Page 2; PM 4 – 09.18

RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends

Kinematic viscosity and vapour pressure: RENISO TRITON SEZ 68 and R134a




All % figures represent mass % oil in the refrigerant/oil mixture.

RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends



Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R404A



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends

Kinematic viscosity and vapour pressure: RENISO TRITON SEZ 68 and R404A




All % figures represent mass % oil in the refrigerant/oil mixture.

RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R407C



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R410A



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends

Kinematic viscosity and vapour pressure: RENISO TRITON SEZ 68 and R417A




All % figures represent mass % oil in the refrigerant/oil mixture.

RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R448A



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R449A



RENISO TRITON SEZ 68

**Synthetic refrigeration oil based on polyol esters (POE)
for HFC/FC and HFO refrigerants – including HFO/HFC
refrigerant blends**


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R450A



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R452A



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R454A



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R454B



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R455A



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R507



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R513A



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R514A



RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends

Kinematic viscosity and vapour pressure: RENISO TRITON SEZ 68 and R23




All % figures represent mass % oil in the refrigerant/oil mixture.

RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends

Kinematic viscosity and vapour pressure: RENISO TRITON SEZ 68 and R290




All % figures represent mass % oil in the refrigerant/oil mixture.

RENISO TRITON SEZ 68

Synthetic refrigeration oil based on polyol esters (POE) for HFC/FC and HFO refrigerants – including HFO/HFC refrigerant blends


Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R1234yf



RENISO TRITON SEZ 68

**Synthetic refrigeration oil based on polyol esters (POE)
for HFC/FC and HFO refrigerants – including HFO/HFC
refrigerant blends**

Miscibility behaviour (miscibility gap): RENISO TRITON SEZ 68 and R1234ze



Die Angaben in dieser Produktinformation beruhen auf den allgemeinen Erfahrungen und Kenntnissen der FUCHS SCHMIERSTOFFE GMBH in der Entwicklung und Herstellung von Schmierstoffen und entsprechen unserem heutigen Wissensstand. Die Wirkungsweise unserer Produkte ist von vielfältigen Faktoren abhängig, insbesondere vom konkreten Einsatzzweck, der Applikation der Produkte, den Betriebsbedingungen, der Bauteilvorbehandlung, eventuellem Schmutzanfall von außen, etc. Aus diesem Grund sind allgemeingültige Aussagen zur Funktion unserer Produkte nicht möglich. Unsere Produkte dürfen nicht in Luft-/Raumfahrzeugen bzw. Teilen davon verwendet werden. Dies gilt nicht, soweit die Produkte vor dem Einbau von Bauteilen in ein Luft-/Raumfahrzeug wieder entfernt werden. Die Angaben in dieser Produktinformation stellen allgemeine, nicht verbindliche Richtwerte dar. Keinesfalls beinhalten sie hingegen eine Zusicherung von Eigenschaften oder eine Garantie für die Eignung des Produkts für den Einzelfall.

Wir empfehlen daher, vor dem Einsatz unserer Produkte mit den Ansprechpartnern der FUCHS SCHMIERSTOFFE GMBH ein individuelles Beratungsgespräch über die Einsatzbedingungen in der Anwendung und die Leistungsmerkmale der Produkte zu führen. Dem Anwender obliegt es, die Produkte in der vorgesehenen Anwendung auf deren Funktionssicherheit zu testen und mit der gebotenen Sorgfalt einzusetzen.

Unsere Produkte werden kontinuierlich weiterentwickelt. Deshalb behalten wir uns das Recht vor, das Produktprogramm, die Produkte und deren Herstellungsprozesse sowie alle Angaben in dieser Produktinformation jederzeit und ohne Vorankündigung zu ändern, sofern keine kundenspezifischen Vereinbarungen existieren, die dem entgegenstehen. Alle früheren Veröffentlichungen verlieren mit Erscheinen dieser Produktinformation ihre Gültigkeit.

Vervielfältigungen jeder Art und Form bedürfen der vorherigen schriftlichen Genehmigung der FUCHS SCHMIERSTOFFE GMBH.

© FUCHS SCHMIERSTOFFE GMBH. Alle Rechte vorbehalten.